



informazioni / information

ultima modifica / last update 17/11/2025

dimensioni / dimensions cm.	peso / weight kg.	materiali / materials	ancoraggio / anchoring
204x50x274		 Legno Trattato Treated Timber	

COMPOSTO DA:

- due montanti in bilamellare sez. cm 9x9
- quattro traverse distanziali in massello sp. mm 43
- pannello cm 150, h cm 92 in perline maschiate sp. mm 20 con cornice "U"
- tetto una o due falde in perline sp. mm 20
- viteria inox coperta con tappi plastici
- Spazio informativo 141x87cm

- "Il materiale utilizzato è la conifera nordica impregnata in autoclave (sottovuoto e pressione) con sali antimuffa ed antimarciume senza cromo. Il tipo di impregnante utilizzato è il TANALITH E conforme a normativa UNI EN 351-1"

COMPOSED BY:

- two uprights made of bilaminar wood sect. cm 9x9
- four spacer crossbeams made of solid wood thickness mm 43
- panel cm 150, h cm 92 made of tapped beads thickness mm 20 with "U" corning
- roof one or two pitches in beaded beads thickness mm 20
- stainless steel screws covered with plastic caps
- information space 141x87cm

- "The material used is Nordic conifer impregnated in autoclave (vacuum and pressure) with anti-mold and anti-mildew salts without chrome. The type of impregnant used is TANALITH E in accordance with UNI EN 351-1."

