


profondità scavi / depth of excavation 60 cm.
profondità scavi / depth of excavation 50 cm.
staffa antitrauma sfuso / bracket for loose safety matting



modifiche / amendments :				scala / scale : —	misure espresse in / dimensions are established in : CM.		HOLZHOF 	
nr°	data/date	pos	descrizione/description	firma sign	tolleranze generali applicate / general tolerances : • sezione/diámetro legno impregnato ± 0.5 (cm) • lunghezza legno impregnato ± 1% (lungh. totale) • lavorazioni legno impregnato ± 0.2 (cm) • componenti in metallo ± 1 (mm) • componenti in materiali plastici ± 1.5 (mm) le colorazioni dei componenti raffigurati sono solo indicative e potranno variare a ns/ discrezione. Il presente elaborato grafico è da ritenersi indicativo. La sua reale fattibilità deve essere preventivamente verificata in loco prima della conferma d' ordine. Nessuna responsabilità pertanto sarà da attribuirsi alla scrivente. The colours that are visible in the rendering are just illustrative and can be modified. The graphic design as well is illustrative, and customers are compelled to verify the equipment's real feasibility before finalizing the order. We do not accept claims for similar themes.		denom. / name : pianta scavi / excavation plant	
01	01/07/21		modifiche dimensionali				nr. dis. / draft nr. : 4730	codice / code : xo11pe
02							luogo / place : Mezzolombardo	
03							data / date : 24/01/2017	
03							esecuzione/verifica/ approvazione : created/checked/approved by : 	