




profondità scavi / depth of excavation 60 cm.



profondità scavi / depth of excavation 60 cm.



profondità scavi / depth of excavation 50 cm.
staffa antitrauma fuso / bracket for loose safety matting

modifiche / amendments :				scala / scale : -		misure espresse in / dimensions are established in : CM.				
nr	data/date	pos	descrizione/description	firma sign	Informazioni generali applicate / general information: • sezione/dimensione legname impregnato ± 0.5 (cm) • lunghezza legname impregnato $\pm 1\%$ (lung. totale) • lavorazioni legname impregnato ± 0.2 (cm) • componenti in metallo ± 1 (mm) • componenti in materiali plastici ± 1.5 (mm) Le colorazioni dei componenti raffigurati sono solo indicative e potranno variare a noi discrezione. Il presente disegno grafico è da ritenersi indicativo. La sua reale fattibilità deve essere preventivamente verificata in loco prima della conferma d'ordine. Nessuna responsabilità pertanto sarà da attribuirsi alla scrivente. The colours that are visible in the rendering are just illustrative and can be modified. The graphic design as well as illustrative, and customers are compelled to verify the equipments real feasibility before finalizing the order. We do not accept claims for similar themes.				denom. / name : pianta scavi / excavations plant	
01									nr. ds. / draft nr. : -	codice / code : xrm84
02									luogo / place : Mezzolombardo	data / date : 20/05/19
03									esecuzione/verifica/ approvazione : created/checked/approved by :	
03										