


profondità scavi / depth of excavation 60 cm.
profondità scavi / depth of excavation 60 cm.



modifiche / amendments :				scala / scale : -		misure espresse in / dimensions are established in : CM.		HOLZHOF	
nr°	data/date	pos	descrizione/description	firma sign	tolleranze generali applicate / general tolerances : • sezione/diametro legname impregnato ± 0.5 (cm) • lunghezza legname impregnato $\pm 1\%$ (lunghezza totale) • lavorazioni legname impregnato ± 0.2 (cm) • componenti in metallo ± 1 (mm) • componenti in materiali plastici ± 1.5 (mm)		In colorazioni dei componenti raffigurati sono solo indicative e potranno variare a noi/ discrezione. Il presente elaborato grafico è da ritenersi indicativo. La sua reale fattibilità deve essere preventivamente verificata in loco prima della conferma d'ordine. Nessuna responsabilità potrà essere attribuita alla springle. The colors that are visible in the rendering are just illustrative and can be modified. The graphic design as well is illustrative, and customers are compelled to verify the equipment's real feasibility before finalizing the order. We do not accept claims for similar themes.		denom. / name :
01	29/06/23		modifiche dimensionali						pianta scavi / excavation plant
02							nr. dis. / draft nr. : 4786a		codice / code : xru 30
03							luogo / place : Mezzolombardo		data / date : 03/07/18
03							esecuzione/verifica/ approvazione :		
							created/checked/approved by :		