


PIANTA ANTITRAUMA IN GOMMA/RUBBER ANTI-TRAUMA PLANT
gomma antitrauma/rubber anti-trauma :

- altezza di caduta $h < 100$ cm mq. 18.76/Fall height < 100 cm sq.m. 18.76
- area libera da impedimenti (nessun cordolo, oggetto o dislivello) minimo prato/terreno naturale/
Area free of obstructions (no curbs, objects or unevenness) minimum lawn/natural terrain

all'interno dell' area di impatto non deve essere presente nessun oggetto, ostacolo o dislivello/
within the impact area there shall be no object, obstacle or height difference



! IN CASO DI ANTITRAUMA COLATO!/ IN CASE OF CAST RUBBER ANTITRAUMA:
L'applicazione del materiale antitrauma colato deve garantire uno spessore uniforme su tutta la superficie di impatto/Application of the poured anti-trauma material should ensure uniform thickness over the entire impact surface.
! Per approfondimenti consultare la scheda sul posizionamento dei cordoli dettagliata in allegato/See the detailed curb placement sheet attached for more details.

Origine/Source

modifiche / amendments :					scala / scale :		misure espresse in / dimensions are established in :		denom. / name :	
nr°	data/date	pos	descrizione/description	autore			cm.		Pianta Antitrauma in Gomma / Rubber Safety Matting Plant	
01									nr. dis. / draft nr. :	code / code :
02									-	xsp162
03									luogo / place :	data / date :
04									Mezzolombardo (TN)	18/12/2024
									esecuzione/verifica/ approvazione : created/checked/approved by :	